



20R serie specifications:

	3120R	3520R	4020R	4520R	5220R
Overall length	130"				
Overall width*	64"~ 72"				
Height with ROPS*	97.9"				
Wheelbase*	70.9"				
Front tread*	50.5"				
Rear tread*	43.6 – 60"				
Ground clearance*	12.7"				
Weight with ROPS	4053 lbs	4053 lbs	4063 lbs	4118 lbs	4123 lbs
Weight with cab				4442 lbs	4400 lbs
ENGINE					
Combustion system	Swirl chamber				
Aspiration	Naturally	Naturally	Turbocharged	Naturally	Turbocharged
Engine output	31 hp@2600	35 hp@2600	40 hp@2600	47 hp@2600	55 hp@2600
No. Of cylinders	3	3	3	4	4
Fuel tank capacity	9.3 gal / 35 L				
PTO power	26.5 hp	29 hp	35.5 hp	42 hp	47.5 hp
PTO speed	540/790				
Steering	Hydrostatic				
Clutch	Dry, single				
Brake	Wet disc				
Transmission Type	Fully synchronized with synchroshuttle				
No of speed	12 front / 12 rear				
Agricultural tires	FRONT: 9.5 x 16 REAR: 12.4X28				
Industrial tires	FRONT: 10-16.5 REAR: 420/70-24				
Turf tires	FRONT: 29X12.5-15 REAR: 44X18.00-20				
3 point hitch	Category I				
Main pump flow	8.9 gal/min			11.1 gal/min	
Lift capacity	3306 lbs				

*measurement and clearance varies with tire options
 Specifications are subject to change without notice.